

Products

Farmex tanks equipped with Farmex blades and containment basin. In the ground water area the containment basin are necessary.

Tank sizes:

1350 L, 1600 L, 2000 L, 2900 L, 3800 L, 5200 L, 6200 L, 7800 L, 9300 L

Standard equipment :

- oil level gauge
- 1 piece of internal thread sleeve (diameter 1,0") in the tanks of 1350L – 3800L
- 2 pieces of internal thread sleeve (diameter 1,0") in the tanks of 5200L and bigger
- Camlock – coupling
- Overfilling protection
- Farmex pump unit with suction pipe, check valve and strainer
- Drain plug
- Lifting loops
- Hatchway

Supplementary accessories:

- Manual pump equipment: hand pump, hose, nozzle, anti-siphon valve, pump cabinet, lock option
- Electrical pump 230V (56L or 70L), gauge and automatic nozzle
- Electrical pump 12V and 24V, without a gauge
- The suction pipe of the electrical pump and fixing parts
- Look more information [FARMEX containment basin](#)

Construction requirements:

- 450 l – 1500 L, KTM 313/85 44

- 2000l and bigger, according to the standard SFS 2733
- Containment basin, according to the standard SFS 2733
- Control: TUKES/Inspecta controlling service
- [Look pictures in the gallery](#)